

ECO SOLVENT

POLO HQ™

6 COLOR
OPTION AVAILABLE

3.2MTR HIGH SPEED ECO-SOLVENT INDUSTRIAL PRINTER

BUILT TO DELIVER GREAT
QUALITY PRINTS QUICKLY



POLO HQ, the high-speed Industrial grade eco-solvent printer is built for speed & quality. At a speed of 1175 sqft/hr, **POLO HQ** displays quality print for mass production supported by IR based effective evaporative drying system to meet the high volume requirement. The 3.2 mtr roll-to-roll eco-solvent printer based on industrial grade jetting assembly ensures accuracy at high speed. The environment-friendly **POLO HQ** is built on heavy duty structure made with high mechanical precision standard to meet the growing requirement of those who want speed with quality.

GREEN TECH INK MECHANISM

Polo HQ is highly eco-friendly and is based on ColorJet's **Greentech** Mechanism, which adheres to international print standards and environmental norms. Born from ColorJet's commitment to green printing, Greentech leverages advanced technology to use eco-solvent inks, ensuring low chemical emissions and reduced environmental and health risks. This approach guarantees optimal print solutions that meet both industry and eco-friendly requirements.



SPECIFICATIONS

			POLO HQ	
Models			GA4425	GA6625
Printing Technology			Drop-on-demand, Piezo Electric inkjet	
Print Head			Grayscale Industrial Grade Jetting Assemblies	
No. of Print Heads			4	6
Media	Width		3300mm	
	Thickness		Maximum 3.00 mm with liner	
	Roll Outer Diameter		Maximum 3.52 m	
	Roll Weight		Maximum 150 Kg	
	Core Diameter		76.2mm , 50.8mm	
	Types		Fabric (Ecosolvent based), SAV, PVC Banner, Backlit Film, Window Film	
Printing Width			Maximum 3200mm	
Inks	Types		Eco Solvent Ink	
	Color		4 Colors	6 Colors
Printing Resolution (dots per inch)			Upto 1440 dpi	
Distance Accuracy			Error of less than ±0.3% of distance traveled, or ±0.3 mm whichever is greater	
Media Heating System			Pre heater and Post-heater, setting range for the preset temperature: 30 to 60°C Dryer Setting range for the preset temperature: 30 to 60°C	
Connectivity			High Speed USB	
Power Requirements			AC 220 V+_10%, 20 A, 50/60 Hz	
Dimensions			4960mm x 950mm x 1580 mm (LxWxH)	
RIP software			Onyx Gamaprint Rip (ColorJet Edition)	
Weight (approx. with stand)			1500 Kgs N.W., 1650 Kgs G.W	
Environmental		Power ON	Temperature: 18 °C to 28 °C, Humidity: 35 to 80%RH (Non-condensing)	
		Power OFF	Temperature: 5 °C to 40 °C, Humidity: 20 to 80%RH (Non-condensing)	
Modes	DPI	Passes	Sqm/hr	Sqft/hr
Mode 1	540 x 720	2	109	1175
Mode 2	540 x 1080	3	73	785
Mode 3	540 x 1440	4	46	495
Mode 4	540 x 1080	6	38	410
Mode 5	540 x 1440	8	26	280



Brochure
Polo HQ
Scan Here